

-
- **Symposium on Supercritical CO2 Power Cycle for Next Generation Systems**
- *March 6, 2007, Massachusetts Institute of Technology, Cambridge, Massachusetts*
-
-
-
-


Overview of Supercritical CO2 Power Cycle and Comparison with Other Cycles

P. Hejzlar

M.J. Driscoll, J. Gibbs, Y. Gong, N. Carstens, S.P. Kao
Massachusetts Institute of Technology



CANES
Center for Advanced Nuclear Energy Systems



DOE support through SNL is acknowledged




Outline

- What is the SCO₂ cycle?
- Why the supercritical CO₂ cycle for new reactors?
- Supercritical CO₂ recompression cycle and its parameters
- What issues need to be resolved?

This is an overall review of the SCO₂ cycle


More details can be found in 2 papers on MIT work on the SCO₂ cycle in:

[Nuclear Technology June 2006 issue](#)



What is supercritical CO2 cycle?

Entire cycle is above the dome, no condensation




- Sometimes term transcritical used
- High efficiency at medium temperatures
 - High density near crit. Point (CP)
 - small compressor work
 - Flat isobar above CP, hence low heat rejection T_{ave}
- Small pressure ratio (2.6 versus 1300 for Rankine)
- High mass flow rate, small vol. flow rate




Property changes near critical point

- Large property changes near critical point



Benefit of high density
(low compression work, small machine)


Drawbacks of c_p variation
(pinch point in recuperator)





But drawback of pinch point inside recuperator


- Large cp variation above the CP
- Difficulties to maintain positive temperature difference between cold and hot streams in recuperator
- **Minimum temperature difference can be reached inside the recuperator and NOT at the inlet or outlet**




Recompression SCO₂ Brayton cycle needed for high efficiency



Supercritical CO₂ Recompression Cycle





Why do we need a new cycle?


- New Gen IV reactors
 - Some reactor concepts have core outlet temperature range where Rankine cycle potential to benefit from higher temperatures is limited
 - Combined fossil cycles achieve much higher efficiencies (60%) than current LWRs; increase of thermal efficiencies for nuclear needed to improve competitiveness
 - **Economics is key goal for new nuclear to make an impact**, high cost also main reason for slowdown of nuclear power plant deployment)
- So far, most effort focused on Gen IV reactor designs, but limited potential in addressing the economy goal
- **Selection of BOP can significantly improve economy** and also improve sustainability



SCO2 cycle and Gen IV goals (Cont')

Capital investment decomposition – typical ALWR

- Other
 - Owners cost
 - spare parts
 - contingencies
 - initial fuel cost
- Indirect
 - design
 - project management
- Rest direct
 - Land
 - heat rejection
 - miscellaneous
 - construction services




Reducing reactor plant equipment cost by 50% has a small impact on spec. cost
Increasing efficiency from 34% to 50% has a large effect on \$/kWe!

Conclusion #1: Competitive economy will require high cycle efficiencies



Efficiency of potential cycle candidates




- Steam cycles have lower efficiency above 550°C, hence employ **Brayton cycles**
- SCO2 achieves same efficiency at 650°C as helium at 850°C, but **needs higher pressure**




Cost benefits from lower temperature

Maximum design pressure for HEATRIC HX

Alloy 800 HT (from Dewson&Thonon, at ICAPP03, paper3213)




- Historically, high temperatures had worse impact on cost than efficiency benefit
- Easier to design HX for **high p and medium T** than for **high T and medium p**
- Less mass, hence lower costs of components



Cost benefit from compact turbomachinery


High pressure \rightarrow small volumetric flow rate



Steam turbine: 55 stages / **250 MW**
Mitsubishi Heavy Industries Ltd., Japan (with casing)


Helium turbine: 12 stages / **560 MW** (300 MW_e)
General Atomics GT-MHR design (without casing)

1 m
▲
Supercritical CO₂ turbine: 4 stages / **450 MW** (300 MW_e)
(without casing)




H2 mission – can H2 be made at medium T?

Nuclear plant (SCO₂-GFR)



Electrochemical plant



Key enabling features:

- Recover heat from H₂ and O₂
- Ohmic heating helps keep cell hot

- Yes and at very attractive efficiencies – 51% at 650°C compared to 47% at 950°C using SI
- IHX material problem eliminated (T=527°C)
- Materials problem for heat transport eliminated (steam line at 100 °C)
- Reactor operates between 473 and 650 °C and only electrochemical plant runs at 900 °C




Why SCO₂ cycle for Gen IV reactors - summary

- It offers potentially substantially improved economy
 - high efficiency at medium temperatures
 - lower capital cost – simplicity, compactness
- It makes possible H₂ production at high efficiencies
- There is experience with materials and operation of CO₂ cooled reactors at medium temperatures (14 British AGRs have operated more than 15 years using CO₂ at 650°C), hence less challenging material development
- It **can achieve high efficiency when applied to all (except water cooled) Gen IV reactor concepts** (sodium, lead-alloy, liquid salt, molten salt-cooled, and direct SCO₂ cooled GFR) while Brayton helium cycle is usable (at high efficiency) only with helium and liquid salt cooled reactors
- **SCO₂ cycle is very attractive candidate for Gen IV reactors**



Optimized design statepoints - advanced design T=650° C

Point	Advanced design	
	P	T
	MPa	°C
1	7.692	32
2	20	60.91
3	19.989	159.11
4	19.948	481.83
5	19.818	650
6	7.919	527.15
7	7.804	168.31
8	7.702	70.89



Depending on realizable compressor and turbine efficiencies

Thermal/net efficiency = 50%-51%/ 47-48%



Note on predicted efficiencies


Predicted efficiencies may not be easy to achieve in practice

Predicted net efficiency: generator, mechanical losses 2%, 1%
at 850°C = 48% at 650°C = 48%

But

efficiency is sensitive to:

- Core bypass flow
- Pressure drops
- Recuperator effectiveness (flow maldistribution)
- Plus leakage and cooling penalty
- Predicted efficiencies will be difficult to achieve!



SCO2 cycle much less sensitive to these penalties!!!



Turbomachinery Design - 600 MW_{th}*


	Main Compressor (radial)	Recompressing Compressor (radial)	Turbine (axial)
Number of stages	2	3	4
Impeller diameter (m)	0.6	0.9	1.2
Total-to-static efficiency (%)	89	89	92

* *By MIT Gas Turbine Laboratory engineers*

- **Turbomachinery is extremely compact and has high efficiency**
- **Good diffusers needed to maximize pressure recovery**
- **Cycle efficiency is sensitive primarily to turbine efficiency**


More details on turbomachinery in a separate session






Recuperators and precooler

- SCO₂ cycle is highly recuperative
 - for 600MWth plant 1400MWt is recuperated
 - hence very compact HXs required
- Large pressure difference (20MPa against 8MPa)
- But moderate temperatures (440°C for high temperature recuperator)
- Cycle is sensitive to HX effectiveness – high effectiveness required
- Heatric's printed circuit heat exchangers are excellent candidates – used for all heat exchangers
- **Separate session dedicated to heat exchangers**



What will the cycle layout look like?

- Challenge of large power rating units
 - Economy of scale favors large ratings of nuclear units
 - Brayton cycle efficiency is sensitive to pressure drops
 - Large mass flow rates result in large ducts, pushing the design envelope of power plant experience
 - Connecting pipes should be short and large diameter
 - Largest high pressure pipes ~30” - unit power rating of Brayton cycles is limited to ~300MWe
 - This is an issue for all Brayton cycles – helium cycle performance even more sensitive to ducting because of lower pressure (2.6MPa versus 7.7MPa on low pressure side)
 - So how to design large SCO₂ PCS unit at high efficiency?




Modules with integral layout (as GT-MHR)

Comparison of S-CO₂ and GT-MHR PCU-integral layout

Volume	S-CO₂/GT-MHR	550/1000m³
Power	S-CO₂/GT-MHR	288/288MWe
Power density	S-CO₂/GT-MHR	0.5/0.3MW/m³
SCO₂ more compact than GT-MHR		


Integral layout

- Very compact
- low Δp (no pipes)
- difficult maintenance
- How to place valves?
- Vertical shaft – problem
- Limit 300MWe – need modules






Distributed layout – 1200MWe 2-loop plant




- Two 600MWe, 1800rpm shafts
- Each served by 4 HX trains, straddling the shaft, two floors
- Indirect cycle, IHX inside containment
- HEATRIC PCHE modules
- Turbine blade stress limits power to 600MWe per shaft
- Double flow turbine 1200MWe possible
- HP ducts limited to 1m
- Efficiency loss due to ducting Δp - 1%

Modularity, inspectability, maintainability




50MWe Power Conversion Unit

- Small units - much simpler layout






Size comparison with Rankine PCS



- **SCO2 cycle very compact**
 - high expansion pressure (7.7MPa versus near vacuum)
 - small volumetric flow rate (high max. pressure of 20 MPa and high density near the critical point)
 - compact PCHEs (HTR – 27MW/m³, LTR – 12MW/m³, Precooler 22MW/m³)
 - SCO2 needs 200m³ of storage tanks for inventory control (compared with 1500m³ for helium Brayton)
- **Expectation – lower capital cost than Rankine cycle**



Issues to be resolved

- Operation at partial load and cycle control; transient/accident response
- Radial compressor design and test of main compressor operation in the vicinity of critical point, operation in two-phase region during transients
- How to prevent dry ice formation in depressurization accidents
- Material compatibility with the supercritical CO₂ (hot high density SCO₂ may attack protective oxide layers)
- Detailed HX design including stresses, development of non-proprietary h & f correlations in zigzag channels
- Turbomachinery detailed design (housing, seals, inlet/outlet ducting and bearing components)
- R&D needs will be discussed in the last session