

Supercritical CO₂
Power Cycles
Symposium

ECHOGEN
power systems

Experimental Demonstration of a Coal Fired Primary Heat Exchanger in a sCO₂-based Power Cycle

Authors

Echogen Power Systems

Dr. Timothy Held
Chief Technology Officer

Jason Miller
Director of Engineering

Kyle P. Sedlacko
Sr. Mechanical Systems Engineer

Brett Bowan
E,I and C Manager

Brigham Young University

Dr. Andrew Fry
Associate Professor, Chemical Engineering

Brian Schooff
PhD Candidate

Rajarshi Roy
PhD Candidate

Reaction Engineering International

Andrew Chiodo
Program Manager

Babcock Power

Michael D. Johnson
Sr. Engineer

Project Team and Discussion Agenda

Project Team

- Brigham Young University
- Reaction Engineering International
- Riley Power, Inc (Babcock Power)
- Echogen Power Systems
- Linde
- San Rafael Energy Research Center (SRERC)

Agenda

- SRERC Test Facility
- L1500 Furnace
- Furnace Modeling
- Primary Heat Exchanger Design
- Testing Campaigns
- Conclusions
- Acknowledgments



San Rafael Swell
39.01656°N, 110.50780°W

SRERC Test Facility

Facility Research Focus:

- Nuclear Reactor & Fuel Processing
- Power Cycle Technologies
- Solar Thermal Energy Systems
- Manufacturing

Facility Upgrades

- Electrical
- Piping
- Cooling System
- Auxiliary systems
 - CO₂ inventory system
 - Safety system and equipment
- Foundations and Facilities

Fig4: Satellite View of San Rafael Energy Research Center Facility with L1500 Furnace.



Fig5: Echogen Power Systems Thermal Management System Installed at SRERC.

Fig6: Linde CO₂ Storage Tank Installed at SRERC.

L1500 Furnace

- 1500kW_{th} pilot-scale entrained flow combustor
- 3-zone configuration: radiative, transition and convective sections.
- Refractory lined
- Dual-register, dual-swirl low-NOx burner
- Equipped with primary, inner secondary and outer secondary air injection.




Fig1: L1500 Furnace general arrangement. Three zone configuration, radiative, transition and convective.



Fig2: L1500 Furnace Burner w/Inlet Fuel Manifold

L1500 Furnace Cont.

- Water-cooled, cross-flow heat exchanger in convective section (shown in foreground).
- A baghouse captures particulate entrained in process air.
- Gravimetric feed system with auger screw
- Fuels for this program consist of natural gas and western US bituminous coal.



Fig3: L1500 Furnace. Convective Section (in foreground) with Exhaust Piping and Cooling Manifold.

CFD Modeling

Impact of Firing Rate

- Increasing the firing rate from 0.879MW to 1.76MW (Param2) was effective in enhancing heat transfer.
- A simultaneous increase in excess air played a crucial role in decreasing peak heat flux.

	Units	Baseline	Param2
Total PHX Duty	MW	0.632	1.143
Maximum Inc. Heat Flux to PHX	W/m2	218,000	196,000

Table1: CFD Results, Baseline and Param2 Cases




Fig7: CFD Heat Flux Comparison, Baseline and Param2 Cases




Fig8: CFD Gas Temperature Comparison, Baseline and Param2 Cases

CFD Modeling

Impact of Extended HX Surface

- Extending the heat exchanger by 2ft decreased peak heat fluxes by nearly 6%, as demonstrated in Param6 compared to Param2.
- Param6 was the selected installation option.

	Units	Param2	Param6
Total PHX Duty	MW	1.143	1.135
Maximum Inc. Heat Flux to PHX	W/m ²	196,000	185,000

Table2: CFD Results, Param2 and Param6 Cases




Fig9: CFD Heat Flux Comparison, Param2 and Param6 Cases

CFD Modeling

Impact of Burner Swirl

- Swirl reduction produced a narrower flame sheet near burner
- Higher peak temperatures observed
- Rapid gas mixing yielded substoichiometric combustion and higher fluxes in some cases

Impact of Staging Air

- Staging air elongates the flame, reducing front-end heat flux
- Downstream mixing issues observed producing substoichiometric combustion
- Higher peak temperature
- Increased incident flux

Impact of Bluff Body

- Addition of the bluff body enhanced mixing while extending heat release
- Observed unfavorable peak heat flux due to intensified mixing

CFD Modeling

Impact of Natural Gas Flame

- Running on 100% natural gas
 - Increased heat fluxes at the near-burner end of the radiant section.
 - Produced a substantial increase in peak tube metal temperatures (from 1100°F to 1400°F)
 - Generated a 10% rise in predicted heat transfer to the PHX.




Fig10: PHX Total Heat Transfer Comparison Between Coal and Natural Gas

PHX Design

Design Conditions:

	Units (USC)		Units (SI)	
CO ₂ Inlet Temperature	°F	779	°C	415
CO ₂ Outlet Temperature	°F	1112	°C	600
CO ₂ Flow Rate	lb/hr	43640	kg/s	5.5
CO ₂ Operating pressure	PSIA	2955	MPa	20.37
Max Allowable Working Pressure	PSIA	3975	MPa	27.41

- Tangent wall design per ASME Sect.I
- Material selection Super 304H
- Limited surface area due to retrofit application.
- Sensible heat transfer presented design challenges
- Managing heat flux is critical for maintaining PHX integrity.



Fig11: Primary Heat Exchanger (PHX) Installation

PHX Design

- Embedded heat flux sensors aid in verifying thermal modeling
 - 6 Locations
 - Qty: 2, Near-wall
 - Qty: 2, Mid-wall
- Flow balancing valves are used to manage flow distribution and maintain desire flux levels.
- Skin thermocouples monitor tube metal temperatures.




Fig12: (Right) Heat Flux Sensor General Arrangement



Fig13: Heat Flux Sensors Installed on PHX Piping.



Fig14: (Right) Flow Balancing Valve Installation with Outlet Header.




Fig15: L1500 Furnace Elevation with Heat Flux Locations.

PHX Design

- Heat transfer model aligns well with test data for the radiant module but significantly differs in the convective section due to observed fouling.
- Thermal resistance assumptions impacted sCO₂ exit temperature predictions.
- PHX efficiency = 60-65% (meets predictions).
- Peak heat input of 1.63MW from fuel.
- Adjusting sCO₂ flow rate demonstrated the capability to achieve full design conditions.




Fig18: Comparison of Heat Transfer to PHX for Coal vs Natural Gas at 1.76MW Firing Rate





Fig19: Test Data Comparison of sCO₂ Exit Temperature Showing Impacts of Reduced Overall Heat Transfer to PHX

PHX Design

- Measured total PHX pressure drop:
 - dP = 4.7bar (68psi)
- Model predicted total PHX pressure drop:
 - dP = 3.6bar (52psi)
- Incorporating valve and piping losses yields a total pressure drop, dP = 4.2bar (61psi, 89%)

- Temperature distribution in the radiant panels aligned well with predictions.



Sensor Position	CO ₂ Temps at Convective Outlet °C	CO ₂ Temps at Radiant Outlet (unbalanced) °C	CO ₂ Temps at Radiant Outlet (adjusted) °C
1	371	552	563
2	370	544	556
3	366	553	565
4	368	547	556
5	367	557	567
6	364	550	555
7	354	551	564
8		556	554
9		61*	59*
10		548	555
11		554	561
12		560	567
13		562	584
14		583	564
15		563	583
16		590	583

Table3: PHX Tube Temperature Distribution Comparison Between Unbalanced and Adjusted Flow Balancing Valves

Testing

Campaign 1 Achievements

- 1.6MW max heat input to PHX.
- 70hrs continuous operation.
- Heat-soaked start-up operation.





Fig20: Process Flow Diagram for sCO₂ Cycle




Fig21: Flow Distribution During Campaign 1 Endurance Testing

Testing

Campaign 2 Achievements

- Additional +70Hrs continuous operation.
- Avg. 1MW of heat input to PHX.




Fig22: Flow Distribution During Campaign 2 Endurance Testing




Fig23: PHX Performance During Campaign 2 Endurance Testing

Conclusions

- Increased heat rate of 1.76MW.
- Peak heat flux maintained below 175,000 W/m².
- Near-burner crossmember arrangement reduces peak heat flux.
- Increased excess air mitigates adiabatic flame temperature.
- Measured data aligns well with model predictions.
- Pressure losses aligned with predictions, and flow distribution improved by adjusting balancing valves.
- Flux sensor readings require further review for accuracy.
- Ongoing testing goals:
 - Obtain full design conditions.
 - Investigate material integrity to reduce risks associated with design and manufacturing.



Acknowledgments

Disclaimer

This material is based upon work supported by the Department of Energy under Award Number DE-FE0031928. This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

CRedit Authorship Statement

Kyle P. Sedlacko: Investigation, Formal analysis, Writing - Review & Editing. **Jason Miller:** Project administration, Funding acquisition, supervision.

Brett Bowan: Investigation, Writing.

Timothy Held: Conceptualization, Funding acquisition, Project administration **Andrew Fry:** Conceptualization, Resources, Supervision, Funding acquisition, Investigation.

Brian Schooff: Investigation, Formal analysis, Writing - Review & Editing. **Rajarshi Roy:** Investigation, Formal analysis, Writing - Review & Editing. **Michael D. Johnson:** Methodology, Formal analysis, Investigation, Writing. **Andrew P. Chiodo:** Investigation, Software, Validation, Formal analysis, Writing – Review & Editing, Visualization