

Start-up Modeling for a 10MWe sCO₂ Primary Power Plant

Shawn Engle
Systems Engineer

Jason A. Mallinak
Senior Systems Engineer

Jason D. Miller
Engineering Manager

Dr. Timothy J. Held
Chief Technology Officer

The logo for ECHOGEN power systems is a large orange square with the word "ECHOGEN" in white, bold, uppercase letters, and "power systems" in a smaller, white, lowercase font below it.

ECHOGEN
power systems

The 7th International Supercritical CO₂ Power Cycles • February 21 – 24, 2022 • San Antonio, TX, USA

The logo for the sCO₂ Supercritical CO₂ Power Cycles Symposium features a stylized green "sCO₂" with a lightning bolt and a leaf, followed by the text "Supercritical CO₂ Power Cycles Symposium" in green.

sCO₂
Supercritical CO₂
Power Cycles
Symposium



Presentation Agenda

- Introduction
 - Fossil Fuel Large Scale Pilots DOE Project
 - Large Scale Pilot sCO₂ Power Cycle
 - Simulation Study Motivation
- Modeling Methodology
- Start-up Modeling
 - Overview
 - Procedure
 - Results
- Summary

Fossil Fuel Large-Scale Pilots


“transformational coal technologies aimed at enabling step change improvements in coal powered system performance, efficiency, and cost of electricity”

- Phase I: Feasibility
 - 9 projects
- **Phase II: FEED**
 - 6 projects
 - **sCO₂ (1 project)**
 - Gasification (1 project)
 - Advanced combustion (1 project)
 - CO₂ capture (3 projects)
- Phase III: Construction/Operation
 - 1–2 projects




Project Team



- Echogen Power Systems
 - Power cycle design and fabrication
 - Turbomachinery design and fabrication 
- Louis Perry and Associates, a CDM Smith Co.
 - EPC – FEED contractor
 - Balance of plant engineering and Phase III construction
- Electric Power Research Institute
 - Economic analysis
 - Test planning and Phase III test support
 - Industry voice
- University of Missouri
 - Host site
 - Permitting
 - Plant operations
- Riley Power
 - Coal-fired heater design and fabrication
 - Air quality control systems (AQCS) design and fabrication


Large Scale Pilot sCO₂ Power Cycle

- **Power Cycle – 10 MW_e nominal**
 - Modified Recompression Brayton Cycle: $\eta = 39.4\%$ (gross), 35.3% (net)
 - Turb. Inlet Temp. = 600°C (1112°F)
 - Turb. Inlet Pres. = 23 MPa (>3300 psig)
- **Process Cooling**
 - Water cooled (existing system)
- **Fired Heater – 32 MW_{th}**
 - Stoker style combustion: $\eta = 84.3\%$
 - CO₂ cooled walls
 - Up to 100% Bituminous coal (Illinois #6)
 - HHV 11,338 Btu/lb
 - Up to 100% Natural gas




Simulation Study Motivation

- LSP applied stoker-fed coal fired heater as sCO₂ power cycle primary heat exchanger
 - Large CO₂ side volume – majority of system volume
 - High heat source temperature
 - Limited ability to control heat input
- Fired heater uses natural gas during start-up and switches to coal firing when CO₂ flow is established
 - Targets CO₂ outlet temperature
- Novel start-up method developed to avoid need to fill fired heater with liquid CO₂ to achieve start-up
 - Minimize CO₂ inventory requirement
- **Transient simulation of 1D LSP system model used to evaluate the effectiveness of novel start-up method**




Modeling Methodology

- Modeling Platform
 - GT-SUITE v2020
- Heat Exchangers
 - Fired Heater (PHX1 + PHX2)
 - Co-simulation Functional Mock-up Unit (Riley Power, Inc.)
 - Printed Circuit Heat Exchangers (CHX, LTR, HTR)
 - Empirical correlations using exchanger geometry
- Turbomachinery
 - Turbines (HTC DT, LTC DT, PT) + Compressors (HTC, LTC)
 - Performance maps (Barber Nichols): isentropic enthalpy change, corrected mass flow rate, corrected speed, and ETA
 - Pumps: positive displacement (TP), centrifugal (SP)
 - Performance map: pressure rise, volumetric flow rate, speed, and ETA (SP)
 - Fixed volumetric ETA and displacement with variable speed (TP)




Start-up Overview

- Start-up process transitions system from initial vapor fill to turbo-compressor (LTC DT + LTC) self-sustaining operation in 3 steps
- Minimize CO₂ inventory requirement
- Avoid two-phase at electrically-driven start pump (SP) inlet
- System CO₂ below saturation pressure of cooling heat exchanger (CHX) process water during start-up
 - CHX acts as evaporator
 - Danger of two-phase inlet to SP
 - Three process water temperatures (T_{cw}) simulated
 - 18 °C, 26 °C, and 32 °C




Start-up Procedure – Step 1

- Liquid CO₂ pumped from inventory (IC Tank) to system through the transfer pump (TP)
- Liquid enters the CHX and boils
 - CO₂ pressure is below saturation pressure at T_{cw}
- Heat and mass addition increases system CO₂ pressure
- Transition to step 2 once system CO₂ pressure reaches saturation pressure at T_{cw}




Start-up Procedure - Step 2

- SP begins to circulate CO₂ through the system with target of 8 kg/s
- PCV0530 used to control SP mass flow rate
- Fired heater gas burners are lit
 - No coal at this stage
 - Heat addition to system through PHX-1
- Fired heater CO₂ outlet temperature target set to 100 °C
- Transition to step 3 when CO₂ pressure at SP inlet reaches target design pressure




Start-up Procedure – Step 3

- Inventory control system (ICS) activates
 - Maintains target SP inlet pressure by addition or subtraction of CO₂ mass
- SP mass flow rate target increased to 20 kg/s
- Fired heater target CO₂ outlet temperature increased to 250 °C






Start-up Results

- Two-phase flow observed at SP inlet during transition from Step 1 to Step 2 for $T_{cw} = 18\text{ }^{\circ}\text{C}$ and $26\text{ }^{\circ}\text{C}$
 - No two-phase in $32\text{ }^{\circ}\text{C}$ case
- Mass flow rate spikes during step transitions
 - Magnitude greater for lower T_{cw} cases




Start-up Results

- Sharp decrease in SP inlet pressure at step transitions
 - Below saturation pressure for step 1 to step 2
 - Two-phase flow at CHX outlet
- Slow pressure rise build across the pump
 - Mass flow rate spikes



Start-up Results


- Add control valve close to SP outlet (PCV)
 - Prevent mass flow rate spikes
 - Eliminate low side pressure dip
- Transition flow rate control back to PCV0530 after Step 3



Start-up Results and Discussion

- 44,850 kg of CO₂ needed to fill the system
- Novel start-up method reduced CO₂ mass required by 44% (worst case)
- Greater reduction predicted with controls refinement and additional control valve

T _{cw} (°C)	PEAK CO ₂ MASS (kg)	PEAK CO ₂ MASS REDUCTION (%)
18	18998	57.6
26	19766	55.9
32	25093	44.1





Summary

- Project team lead by Echogen Power Systems awarded funding for a phase II FEED study of a proposed stoker-fed, coal-fired, 10MW_e sCO₂ Economized Recompression Brayton Cycle Primary Power Large-Scale Pilot Plant as part of the DOE Fossil Fuel Large-Scale Pilots program
- Novel start-up method was developed in response to the application of a stoker-fed coal fired heater as sCO₂ power cycle primary heat exchanger
- Transient simulation of 1D LSP system model used to evaluate the effectiveness of the novel start-up method
- Start-up method reduced required CO₂ inventory by 44% over filling the fired heater with liquid CO₂
- Control valve at SP outlet should be added to prevent two-phase flow at SP inlet and improve CO₂ inventory reduction



Acknowledgement and Disclaimer

- This material is based upon work supported by the Department of Energy under the Award Number DE-FE0031585.
- This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.