



# sCO<sub>2</sub> Power – Status and Outlook for Technology Maturation

---

John Marion – GTI R&D Programs Sr. Director

Industry Panel – 7<sup>th</sup> International sCO<sub>2</sub> Symposium

February 22, 2022

San Antonio, TX



# Working with Industry and Governments to Build and Demonstrate Low-Cost, Low-Carbon, Efficient Energy Systems



**World-class piloting facilities headquartered in Chicago area**

-   
RESEARCH & DEVELOPMENT
-   
PROGRAM MANAGEMENT
-   
TECHNICAL/ANALYTICAL
-   
CONSULTING
-   
TRAINING
-   
COMMERCIALIZATION
-   
EMPLOYEES

**400+**



# sCO<sub>2</sub> Power Cycles

## Promise:

- Efficient, Cost effective, Compact, Scalable, low water, low-carbon power generation

## Challenges:

- Operability, Transients, Turbomachinery aerodynamic performance, seals, recuperator size & durability, materials, cost

## Versatile Technology – Broad Applicability:



Concentrated Solar



Fossil Fuel



Geothermal



Nuclear



Energy Storage



Waste Heat Recovery

## STATE OF DEVELOPMENT




EPS100 Echogen ~3.1 MWe, ~270°C



STEP (late '22) 10 MWe, 500 & 715°C



NetPower LaPorte TX, 25 MWe, ~1150°C



Sunshot SwRI/GE 1 MWe ~715°C

# Challenges to mature sCO<sub>2</sub> Power Cycles

Key focus points to mature sCO<sub>2</sub> power technology:

- Performance & Operability
- Cost
- Component readiness

## STEP project contribution



Concentrated Solar



Fossil Fuel



Geothermal



Nuclear



Energy Storage



Waste Heat Recovery


# Performance and Operability

STEP 10 MWe Pilot Demonstration Facility

- Test verification
- Models – static and dynamic
- Simulators for operators
- Scale-up:
  - Turbine efficiency improvement
  - Specific costs (\$/KW) improvement



GTI sCO<sub>2</sub> FlowNex® dynamic model with GE Mark VI simulator



GTI AspenPlus® steady state modeling


Model Names	Cycle Configuration	Description	Load %	Net Power Level (MWe)	Cooler Exit Temperature	Turbine Inlet Temperature	Cycle Efficiency
133	Simple	Simple cycle minimum load case	Min	2.5	35°C	500°C	22.6%
136	Simple	Simple cycle maximum load case	Max	6.4	35°C	500°C	28.3%
151	Recompression	Baseline case	100%	10.0	35°C	715°C	43.4%
152	Recompression	"Hot" Day Case	70%	6.6	50°C	675°C	37.4%
153	Recompression	"Cold" Day Case	100%	9.9	20°C	525°C	36.8%
154	Recompression	Partial load case using inventory control	40%	4.0	35°C	715°C	37.0%
155	Recompression	RCBC at 500°C turbine inlet temperature	70%	6.9	35°C	500°C	32.5%
157	Recompression	Partial load case using TSV throttling (transient condition)	40%	4.2	35°C	715°C	30.8%
157a	Recompression	Partial load case using TSV throttling	40%	3.9	35°C	675°C	29.6%

# Cost


- **Mature supply chain**
  - Confidence with experience (performance, manufacturing processes, time & costs, and equipment reliability)
- **Material Options**
  - 740H, H282, IN625, IN617, etc
  - Mfg and repair
- **Plant arrangement**
- **Improved components**  
(next slide)



IN740 Welding for STEP heater to ASME PVC



5-axis EDM STEP turbine



Adv Alloys - ASME allowable stress \*



Haynes 282 casting for STEP TSV




Compact arrangement example  
Echogen EPS100

# Component readiness

- **Power Turbine**

- Seals, thermal mgmt, aerodynamics, OEM product development



STEP HTR – 316S – 49 MW<sub>th</sub>, 600°C

- **Compressor**

- Flexibility, 2-phase start-up, OEM confidence



STEP 715°C  
Haynes 282  
TSV

- **Heat Exchangers**


- Scale-up, fabrication experience, integrity

- **Valves**

- Operational experience, seals, materials choices



STEP Compressor IGVs



Compressor start-up with liquid phase CO<sub>2</sub>

# STEP Project





## Scope:

Design, construct, commission, operate 10 MWe sCO<sub>2</sub> Pilot Plant Facility  
 - reconfigurable to accommodate other testing

## Objectives:


- Demonstrate pathway to efficiency > 50%
- Demonstrate operability at 500°C & ≥700°C turbine inlet temperature with 10 MWe net power generation
- Verify System Performance & Operability:
  - Quantify component and system performance
  - Demonstrate operation across control parameters
  - Measure transient response through start-up, load change, and shutdown



### Simple Cycle

- Shortest time to initial data
- Controls & safety
- Component performance
- Steady & transient cycle data

T<sub>IT</sub> 500°C, 250 bar



### Recompression Cycle

- Inventory management
- Starting transients
- Parallel compressor control
- SOA component efficiencies
- Cycle efficiency > 50%

T<sub>IT</sub> 715°C, 250 bar





# sCO<sub>2</sub> Technology Maturation – Summary

STEP pilot contribution & future needed [High Temperature Indirect sCO<sub>2</sub> power]



Technology	STEP pilot	Future	
Perf. Verification	😊	with commercial products	key objective for STEP
Plant Operability	😊	with commercial applications	key objective for STEP
Static & Dyn. Modeling	😊	refine with data	Developed and validated on STEP
Supply Chain	😐	gain experience & confidence	Immature now and should come with market
Materials (design & use) 740H welding 282 casting 625 welding	😐	gain experience	STEP applying ASME available and guidance
	😊		
	😐		
	😊		
Plant Arrangement	😞	with commercial application	STEP arrangement flexible not compact
Turbine	😐	commercial products	STEP turbine is technology development not product development
Compressor	😊	gain experience & confidence	STEP compressor specification evolved with learnings
Heat Exchangers	😊	gain experience & confidence	STEP heat exchangers push scale
Valves	😊	gain experience & confidence	STEP valves adapted from steam plants



# Gratefully Acknowledging the Support from U.S. DOE-NETL and Project Partners





## Disclaimer

This presentation was prepared by GTI as an account of work sponsored by an agency of the United States Government. Neither GTI, the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors herein do not necessarily state or reflect those of the United States Government or any agency thereof.

# Turning Raw Technology into Practical Solutions

[www.gti@energy](http://www.gti@energy)  
[www.STEPdemo.us](http://www.STEPdemo.us)



[jmarion@gti.energy](mailto:jmarion@gti.energy)

