



# Operational Transients in Supercritical CO<sub>2</sub> Systems: A Case Study on a 10 MWe Cycle

George Khawly, P.E. (SwRI)  
Joshua Warren (SwRI)  
Craig Nolen (SwRI)  
J. Jeff Moore, PhD (SwRI)  
Mark Winqvist (GTI Energy)  
Sergio Meza (GTI Energy)

Paper #61



# Supercritical Transformational Electric Power (STEP) Demo Project



## • Objectives:

- Advance sCO<sub>2</sub> power from TRL3 to TRL7
- Demonstrate pathway to net plant efficiency > 50%
- Demonstrate control and operability at **500°C** and **715°C** turbine inlet temperature with **10 MWe** power generation

## • Accomplished:

- Simple Cycle (SC) operation – 4 MWe to grid
- Reconfiguration to RCBC – Final stages of installation

## • Project Partners:



[www.STEPdemo.us](http://www.STEPdemo.us)



GTI ENERGY



GE VERNOVA



PETROBRAS




Natura Resources  
Canada





# sCO<sub>2</sub> Power Cycle: 10 MWe Case Study




## Reciprocation Closed Brayton Cycle (RCBC)

- 10 MWe net
- 2 Compressors
- 2 Recuperators
- 2 Coolers (cooler for bypass comp. not shown)

## Simple Recuperated Brayton Cycle (SC)

- 5 MWe net
- 1 Compressor
- 1 Recuperator
- 1 Cooler




Common equipment: Turbine, Natural Gas fired indirect heater, valves, evaporative cooling tower, Inventory system, electrical distribution equipment



# Transient Operation Challenges

Natural gas, indirectly fired sCO<sub>2</sub> heater

- Must comply with NFPA codes
- Leads to fast cooling during shutdown/trip
- Slow ramp when increasing heater outlet temp:
  - 55°C/hr (0.9°C/min) below 260°C
  - 110°C/hr (1.8°C/min) above 260°C
- Rapid transient during hot startup
  - +40°C/min followed by -60°C/min





Heater outlet temperature during hot startup followed by a normal shutdown




# Startup Dynamics: Liquid Stagnation

- During overnight shutdowns, ambient cooling allows liquid to form in “cold” section piping
- As compressor begins rotation, liquid “slug” moves around loop and creates oscillations in pressure and temperature
- Low-speed roll implemented to allow removal of liquid (and thereby 2-phase flow) by heat addition
- Period of oscillation pattern follows approximated circulation cycle






# Startup Dynamics: Isenthalpic Expansion



- Compressor provides pressure build prior to flow through the turbine
- Initial flow through turbine is cooled due to isenthalpic expansion
  - Can produce liquid CO<sub>2</sub>
- Firing the heater helps eliminate this risk however, heater controls require minimum CO<sub>2</sub> flow prior to firing



# Shutdown Dynamics




Normal shutdown sequence at the STEP Demo facility in San Antonio

- Normal shutdown sequence allows for slow cooling of equipment and depressurization
- Emergency stops add much more complexity due to fast reaction requirements
  - Anti-surge controls
  - Potential PSV actuation
  - Machinery protection (like DGS's)
- Recommend to add minimum wait time for certain E-stops to prevent thermal shocks



# Component Design Implications




- Operating profile and expectations should be determined at an early stage of design
  - Fast start capability
  - Rapid load transients
  - Code requirements impact (such as NFPA)
- Modeling should be employed to estimate design life due to rapid transients
  - See ~41000s in figure peaks at ~300°C and comes back below 50°C at following start



# Component Design Implications

- Identify localized system requirements, not only most restrictive equipment
- Turbine control valve outlet temp experienced several fast-cooling events similar to data shown
  - Led to premature cracking and loss of sealing at valve seat
  - More details in paper #69





# Summary

- Identify operating scenarios early
  - Code compliance
  - Expected transients
    - Startup
    - Shutdown
    - Emergency stops
- Safety considerations
- Verify physics and thermodynamic processes
  - Closed or open system
  - Phase change phenomenon
  - Joule-Thomson effects
  - Compressibility effects

Cycle configurations must be considered independently



# Gratefully Acknowledging the Support from U.S. DOE-NETL and Project Partners



[www.STEPdemo.us](http://www.STEPdemo.us)



# Questions?

## Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.